



SPECIFICATION SHEET – DPF & DP (DREDGE PUMP) SERIES



PUMP MODEL	DISCHARGE BORE	DISCHARGE HEAD	CAPACITY	MAX. SOLID SIZE	MOTOR			WT.	SYN. SPEED	DIMENSIONS			RECOMMENDED GENERATOR CAP	
					OUT PUT	POLES				A	B	C		
	mm	Mtrs	M3/min	mm	KW	HP		Kgs	RPM	mm	mm	mm	DOL	RS
DPF-15	100	15	1.5	35	11	15	6	490	1000	1295	1100	750	50	-
DPF-15B	150	8	3.2	60	11	15	6	530	1000	1295	1100	840	50	-
DPF-20	100	20	1.5	35	15	20	6	550	1000	1310	1100	825	70	-
DPF-20H-1	100	25	1.5	30	15	20	6	550	1000	1310	1100	825	70	-
DPF-20B	150	10	3.2	60	15	20	6	540	1000	1310	1100	840	70	-
DPF-30	100	30	1.5	35	22	30	6	750	1000	1390	1200	910	100	-
DPF-30B	150	15	3.2	60	22	30	6	730	1000	1390	1200	955	100	-
DPF-40B	200	12	6	40	30	40	6	750	1000	1390	1200	1010	130	-
DPF-50	150	25	3.2	60	37	50	6	950	1000	1575	1350	1020	175	125
DPF-50H	150	28	3.2	40	37	50	6	950	1000	1580	1350	1094	175	125
DPF-50B	200	15	6	60	37	50	6	970	1000	1575	1350	1065	175	125
DPF-50BL	250	5	12	100	37	50	6	1150	1000	1650	1450	1350	175	125
DPF-75B	200	28	6	60	55	75	6	1020	1000	1670	1450	1145	225	175
DP-100B1	200	30	6	60	75	100	8	2300	750	1875	1650	1570	275	225
DP-100BL	250	15	12	100	75	100	8	2700	750	2058	1850	1645	275	225
DP-150	200	40	6.5	120	110	150	10	3500	600	2734	2300	1610	360	300
DP-150L	200	30	8	120	110	150	10	3500	600	2734	2300	1610	360	300
DP-150B	250	22	12	120	110	150	10	3500	600	2794	2400	1695	360	300

DOL = DIRECT ON LINE R.S = REACTOR STARTER(O.E)

CAB TIRE CABLE	
DPF 15 TO DPF 20	3PNCT 8MM2 X 4C
DPF 30, 30B	3PNCT 14MM2 X 4C
DPF 40B	3PNCT 22MM2 X 3C & 3.5MM2 X 1C

CAB TIRE CABLE	
DPF 50 TO DPF 75	3PNCT 38MM2 X 3C & 3,5MM2 X 1C
DP-100	3PNCT 100MM2 X 3 C & 8,0MM2 X 1C
DP-150	3PNCT 100MM2 X 3C & 14MM2 X 1C